

## TECHNICAL INFORMATION

# TRUXES ADHESIVES

### HOT MELT ADHESIVES

### FOR FILTER MANUFACTURING

PRODUCT	APPLICATION	SOFT. PT. <sup>1</sup> °F(°C)	VISCOSITY <sup>1</sup> cps @ 350°F	COLOR (GARDNER)
<b>FILTER PLEATING</b>				
TR-1162	MINI-PLEATS	200(93)	5500	WHITE (1)
TR-3162	HI-TEMP	230(110)	5500	WHITE (1)
PF-3165 <sup>2</sup>	HIGH STRENGTH FLEXIBLE	220(105)	7000	WHITE (1)
<b>FILTER ASSEMBLY</b>				
TR-1137	NON-POROUS SUBSTRATES	160(71)	700	OFF-WHITE (2)
HM5-11/21	HI-TEMPERATURE SPIRAL WRAP	285(140)	2200	WHITE (1)
HM9-10	ASSEMBLY (LONG OPEN TIME)	225(110)	2000	WHITE(1)

<sup>1</sup> approximate

<sup>2</sup> possible use in fire retardant applications

**Note: All above products are FDA Food Grade Adhesives**

For additional information, or to request a sample, call toll-free 888/554-8448.

To the best of our knowledge the above information is accurate. However, it is the purchaser's responsibility to determine this accuracy, and the suitability, if any, of our products in their applications.

Truxes Company  
16 Stone Hill Road ▪ Oswego, IL ▪ 60543 ▪ USA

Tel: 630/554-8448  
Fax: 630/554-8453

SPECIALTY ADHESIVE MANUFACTURING SINCE 1976