

## TECHNICAL INFORMATION

**TRUXES ADHESIVES**

PRODUCT: **TR-1018**

DESCRIPTION: **HOT MELT ADHESIVE**

Applications:

Aggressive pressure sensitive for product assembly, permanent labeling and packaging. May be sprayed, extruded or roll coated.

Properties:

Physical Form	Brickettes in release trays
Solids	100%
Color	Caramel
Odor	Mild Acetic
Set Time	Indefinite hot and cold tack
Viscosity	Approx. 4200 cps @ 275°F(135°C)
Specific Gravity	.98
Softening Point	Approx. 175°F (80°C)
Operating Temperature	350°F(177°C)
FDA Status	21CFR175.105 Adhesives
Shelf Life	Indefinite if kept dry and clean

Handling and Storage:

Use of general ventilation recommended. Keep container closed after opening to avoid contamination. There are no health hazards in solid form; however once melted, adhesive can cause severe burns. If molten material comes in contact with skin, flush area immediately with cool water and obtain medical attention. For additional information or the Material Safety Data Sheet call tollfree 888/554-8448.

To the best of our knowledge the above information is accurate, but it should not be construed as a warranty. All implied warranties are expressly disclaimed. It is the purchaser's responsibility to determine this accuracy, and the suitability, if any, of our products in their applications.

Truxes Company  
16 Stonehill Road ▪ Oswego, IL ▪ 60543 ▪ USA

Tel: 630/554-8448  
Fax: 630/554-8453

**SPECIALTY ADHESIVE MANUFACTURING SINCE 1976**