

## TECHNICAL INFORMATION

**TRUXES ADHESIVES**

PRODUCT: **TR-1137**

DESCRIPTION: **HOT MELT ADHESIVE**

Applications:

Labeling, packaging, bookbinding, gasket forming and product assembly.

Properties:

Physical Form	Brickettes in release trays
Solids	100%
Color	Off White
Odor	Mild Acetic
Set Time	Medium
Viscosity	Approx. 1200 cps @ 325°F(163°C)
Specific Gravity	.97
Softening Point	Approx. 160°F (71°C)
Operating Temperature	300°F(149°C) to 350°F(177°C)
FDA Status	21CFR175.105 Adhesives
Shelf Life	Indefinite if kept dry and clean

Handling and Storage:

Use of general ventilation recommended. Keep container closed after opening to avoid contamination. There are no health hazards in solid form; however once melted, adhesive can cause severe burns. If molten material comes in contact with skin, flush area immediately with cool water and obtain medical attention. For additional information or the Material Safety Data Sheet call tollfree 888/554-8448.

To the best of our knowledge the above information is accurate, but it should not be construed as a warranty. All implied warranties are expressly disclaimed. It is the purchaser's responsibility to determine this accuracy, and the suitability, if any, of our products in their applications.

Truxes Company  
16 Stonehill Road ▪ Oswego, IL ▪ 60543 ▪ USA

Tel: 630/554-8448  
Fax: 630/554-8453

SPECIALTY ADHESIVE MANUFACTURING SINCE 1976