

TECHNICAL INFORMATION

TRUXES ADHESIVES

PRODUCT: **TR-1144**

DESCRIPTION: **HOT MELT ADHESIVE**

Applications:

Most packaging, tray erection and carton/case sealing.

Properties:

Physical Form	Small Brickettes
Solids	100%
Color	White/Clear
Odor	Practically odorless
Set Time	Fast
Viscosity	Approx. 1200 cps @ 350°F(177°C)
Specific Gravity	.91
Softening Point	Approx. 180°F (82°C)
Operating Temperature	325°F(162°C) to 375°F(177°C)
FDA Status	21CFR175.105 Adhesives
Shelf Life	Indefinite if kept dry and clean

Handling and Storage:

Use of general ventilation recommended. Keep container closed after opening to avoid contamination. There are no health hazards in solid form; however once melted, adhesive can cause severe burns. If molten material comes in contact with skin, flush area with cool water and obtain medical attention. For additional information or the Material Safety Data Sheet call tollfree 888/554-8448.

To the best of our knowledge the above information is accurate, but it should not be construed as a warranty. All implied warranties are expressly disclaimed. It is the purchaser's responsibility to determine this accuracy, and the suitability, if any, of our products in their applications.

Truxes Company
16 Stonehill Road ▪ Oswego, IL ▪ 60543 ▪ USA

Tel: 630/554-8448
Fax: 630/554-8453

SPECIALTY ADHESIVE MANUFACTURING SINCE 1976